

HD-SDI HIGH PERFORMANCE SPEED DOME WITH IR LED (CTJY15CDH55WI-20W)

FEATURES

- Full HD: 1080p video resolution with HD-SDI output
- True PTZ: Pan: 360° / Tilt: -10°~90° with auto flip
- Easy Install: Suspended quick installation structure
- Easy Setup: Full function by OSD control
- Flexible: Camera module selectable
- IP66 water proof
- Level 2 lightning protection
- 3KV surge protection



CTJY15CDH55WI-20W SPECIFICATIONS

| CAMERA | |
|----------------------|---|
| EFFECTIVE PIXEL SIZE | 1920(H)x1080(V) Full HD |
| SENSOR | 1/3" Panasonic CMOS Sensor |
| VIDEO OUTPUT | BNC x 1 for HS-SDI, conform to SMPTE292M |
| LENS | 20X Zoom ICR Lens, f= 4.7~94.0mm / F1.6(W)~F3.5(T) |
| S/N RATIO | Ration 50db (AGC off) |
| MIN. ILLUMINATION | 0.001Lux |
| SHUTTER SPEED | 1/25(30) ~ 1/60,000 sec |
| AGC | Yes |
| WHITE BALANCE | Auto / Manual / One push / indoor/ outdoor |
| BLC | BLC / WDR/ Off |
| DAY / NIGHT | Auto / Day (colour) / Night (ICR, B/W) |
| IR LEDS | 10 pcs |
| IR RANGE | Up to 150m |
| PTZ | |
| PAN / TILT DEGREE | Pan: 360° (endless); Tilt: -10° ~ 90° (auto-flip) |
| PAN / TILT SPEED | Go to Preset Speed is up to 360°/ sec |
| PRESET POINT | 255 presets (label) |
| AUTO SCAN | 8 auto scan tracks, user-defined left and right boundaries and scan speed |
| AUTO TRACKING | Supported |
| PATTERN | 4 patterns, each with 500 instructions or 600s path |
| SEQUENCE | 8 sequence, each with 32 preset points, user-defined dwell time |

SOLE AGENT:



| GENERAL | |
|--------------|--|
| CONNECTORS | RS485 |
| OSD | Menu/ PTZ information |
| PROTECTION | IP66 water proof, Level 2 lightning protection, 3KV surge protection |
| POWER | DC12V / 5A |
| WEIGHT | 6.3kg |
| WIPERS | Yes |
| FAN & HEATER | Yes |

SOLE AGENT:



JIA YING TRADING PTE LTD
佳映贸易私人有限公司

Address: 1 Rochor Canal Road, #02-67/69/34/35/36/37,
Sim Lim Square, Singapore 188504 **Tel:** 6336-0404 **Fax:** 6338-0404
Email: jjaying@singnet.com.sg **Website:** <http://www.jiaying.com>