

DIGITAL VIDEO RECORDER (15-082M/ 15-162M)

FEATURES

- H.264 video compression
- Triplex: concurrent recording/ live-time & playback operation
- Per channel recording quality/ rate adjustment
- Support CMS (Central Management System)/3GPP
- Audio Backup / Audio Streaming
- Graphic User Interface (GUI)
- Support time-point backup function under Ethernet remote control mode



15-082M/ 15-162M SPECIFICATIONS

MODEL	15-082M	15-162M
PERFORMANCE	Triplex (recording, live-time & playback)	
VIDEO		
COMPRESSION	H.264 compression	
VIDEO INPUT	8 x BNC	16 x BNC
VIDEO LOOPING	8 x BNC	16 x BNC
VIDEO OUTPUT	1xMain Monitor, 1xSpot Monitor, 1xS-video, 1X VGA	
REC. RESOLUTION	720x288 (PAL) / 360 x 288 (PAL)	
RECORDING RATE	100 fps (720x288) , 200 fps (360x288)	
RECORDING MODE	Manual, Scheduled (5 Recording Schedule)	
SEARCH MODE	Schedule, Event (Motion, Alarm)	
STORAGE	2 x SATA 3.5" HDD	
BACKUP	1 x USB 2.0 Slot For External USB Drive / HDD / CD-RW / DVD-RW	
UPGRADE	Firmware Upgrade (USB FlashDrive)	
CONNECTION	1 x RJ-45 Ethernet	
PROTOCOLS	Static IP, Dynamic IP, PPPoE	
IE REMOTE	Management, Monitoring, Recording, Playback	
3GPP	Yes	
PTZ PROTOCOLS	1 x RS-485 (Pelco P, Pelco D & etc.)	
ALARM IN/OUT	4x In, 1 x Out	16x In, 1 x Out
MOTION DETECT	Yes (30x24 grids)	
USER INTERFACE	Front Panel Buttons, IR Remote Controller, USB Optical Mouse	
AUDIO INPUT/ OUTPUT	1 x RCA In, 1 x RCA Out	
PHYSICAL		
OPERATING TEMPERATURE	0 ~ 45 °C	
HUMIDITY	0 ~ 90%	
DIMENSION	430x 88 x 382 mm	
WEIGHT	6.5 kg (without HDD)	
POWER	DC 12 V	

SOLE AGENT: